FerroPip

CARBON

Ferritic Piping Solutions

sales@ferropipe.com

Seamless Pipes

API 5L Grade X56 PSL1

Specification for line pipe

Material Description

API 5L Grade X56 PSL1 Carbon Steel Seamless Pipes are carbon steel pipes, strictly manufactured as per API (AMERICAN PETROLEUM INSTITUTE) to meet the clients requirements.API 5L Grade X56 PSL1 carbon steel pipes are provided with multiple end connections like non-Upset ends and External Upset Ends.Ferropipe provides these api pipes with all mandatory non-destructive testing inclusive of eddy current tests, hydro testing. We offer API 5L pipes with both galvanized and black finish in single random length i.e. 4-7 metres and double random lengths i.e. 7-13 metres. In General these api pipes are used to transit oil .gas and petroleum distilleries. Ferropipe is exclusively engaged in stocking and manufacturing API 5L Grade X56 PSL1 carbon steel Pipes with certifications confirming to EN 10204- 3.1/3.2 with third party inspection services approved by TUV.DNV.SGS,LLOYDS,EIL.API 5L Grade X56 PSL1 Carbon Steel Seamless Pipes are used to convey oil,gas & water in petroleum & gas industries.API 5L Grade X56 PSL1 pipes are available in seamless and welded types, commercially known as API 5L line pipes.

Chemical Properties

Carbon	Silicon	Manganese	Phosphorous	Sulphur	Molybdenum	Nickel	Chromium	Copper	Other Elements
0.28	-	1.4	0.03	0.03	-	-	-	-	-

Mechanical Properties

Yeild Stress	(O.2% Offset)		Tensile Strength		Elongation
min MPa	min MPa	min MPa	max MPa	min ksi	A5 min
386	-	490	-	-	-

Production Programme Certifications The diameter, tolerances and surface finish of component Pipes and Tubes manufactured as per API 5L Grade X56 PSL1 are certified with En 10204 are the same as those stated for the full length tube. Type 3.1/3.2. IBR,NACE,HIC,IGC,IMPACT are adhered as supplementary testing Outer diameter: 6.25-1800mm Nominal Dia: 1/4"-72" requirements. Schedule: 10 - XXS / Thk 1mm-150mm Single random Lengths: 4-7 meters Double random Lengths: 7-13 meters Product Marking Chamfering can be done at fixed lengths. Each Pipe/tube is marked with tube type, heat number, steel grade and size. Other Pipes are externally varnished with black paint or Bare. markings, such as stamping, can be made on request. Hot deep Galvanised Pipes with threaded ends are provided.

Reference Documents

Equivalent Designation

-	European Standard -	DIN Specification DIN 17172 StE 385.7
Related Keywords	ASME Specification	ASTM Specification -
Carbon Steel Pipe, Ferritic Steel Pipe, Carbon Steel Seamless Pipe, Api 5L Grade X56 Psl1 Seamless Pipe, X56 Psl1 Pipe, Seamless Steel Pipe, Ferritic Carbon Steel Pipe, Api 5L Seamless Pipe, Seamless Pipe, Steel Pipe	British Standard -	Japanese Standard -

Pipes Make: ISMT, MSL, JSL, TATA, BHUSHAN, JINDAL, SUMITOMO, TENARIS, ARCELOR MITTAL

#4/217, Deccan Bank Bldg, R. R. Roy Road, Mumbai – 400 004. Maharashtra, INDIA

India's Largest Stockist & Dealers of Carbon Steel Pipes & Alloy Steel Pipes

sales@ferropipe.com 00-91-22-66157017 www.FerroPipe.com Copyright 2015 FerroPipe